



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum	length max	
															
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
1435183	30	1-3/16	40	1,58	10	150	30	450	0,61	0,41	125	4,9	0,9	60	200
1388444	32	1-1/4	42	1,65	10	150	30	450	0,74	0,50	135	5,3	0,9	60	200
1389025	35	1-3/8	45	1,77	10	150	30	450	0,80	0,54	145	5,7	0,9	60	200
1386190	38	1-1/2	48,5	1,91	10	150	30	450	0,89	0,60	165	6,5	0,9	60	200
1430718	40	1-37/64	50	1,97	10	150	30	450	0,93	0,63	170	6,7	0,9	60	200
1386204	51	2	62	2,44	10	150	30	450	1,26	0,85	230	9,1	0,9	60	200
1388410	63,5	2-1/2	75,5	2,97	10	150	30	450	1,73	1,16	290	11,4	0,9	60	200
1386174	76	3	89	3,51	10	150	30	450	2,18	1,46	360	14,2	0,9	60	200


IT

Tubo per aspirazione e mandata olio idraulico

Applicazione: tubo spiralato con copertura grecata progettato per aspirazione e mandata di olio con contenuto aromatico fino al 30% nei sistemi idraulici, escluso olio a base di estere.

Temperatura: da -20°C a +100°C.

Costruzione

Sottostrato: gomma sintetica nera, liscia.

Rinforzo: tessuti sintetici ad alta resistenza, spirale d'acciaio incorporata.

Copertura: nera, grecata in gomma sintetica, resistente agli agenti atmosferici.

EN

Hydraulic oil suction and delivery hose

Application: square corrugated hose used for the suction and delivery of oil with aromatic content up to 30% in hydraulic systems, excluding oils with ester base.

Temperature: from -20°C (-4°F) to +100°C (+212°F).

Construction

Tube: black, smooth, synthetic rubber.

Reinforcement: high strength synthetic cord plus steel helix wire.

Cover: black, square corrugated, synthetic rubber, weathering resistant.