



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum	length max	
															
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
1380354	32	1.1/4	44	1.73	16	240	48	720	1,11	0,75	135	5,3	0,9	120	400
1375873	38	1.1/2	52	2,05	16	240	48	720	1,54	1,04	165	6,5	0,9	120	400
1371649	51	2	66	2,60	16	240	48	720	2,06	1,38	230	9,1	0,9	120	400
1374834	63,5	2.1/2	78,5	3,09	16	240	48	720	2,65	1,78	290	11,4	0,9	120	400
1371720	76	3	91,5	3,61	16	240	48	720	3,18	2,14	360	14,2	0,9	120	400
1395190	90	3.35/64	107,5	4,24	16	240	48	720	4,42	2,97	450	17,7	0,9	120	400
1371746	102	4	119	4,69	16	240	48	720	4,92	3,31	515	20,3	0,9	120	400
1400479	127	5	148,5	5,85	16	240	48	720	7,53	5,06	700	27,6	0,9	60	200
1391801	152	6	180	7,09	16	240	48	720	12,31	8,27	900	35,5	0,9	60	200
1395157	203	8	234	9,22	16	240	48	720	17,83	11,98	1200	47,3	0,9	60	200


IT

Tubo per aspirazione e mandata carburanti ed olio

Applicazione: tubo spiralato liscio, utilizzato per mandata e aspirazione di prodotti petroliferi con contenuto aromatico fino al 50%.

Temperatura: da -20°C a +70°C.

Costruzione

Sottostrato: nero, liscio, in gomma NBR.

Rinforzo: tessuti sintetici ad alta resistenza, treccia rame antistatica e spirale d'acciaio incorporate.

Copertura: nera, liscia (ad impressione tela), in gomma sintetica resistenti agli agenti atmosferici ed all'olio.

Marcatura: transfer ad elica di colore rosso "OIL (logo applicazione) PUERTORICO S&D 16 BAR 235 PSI S.F. 3:1 (Striscia IVG + sito Web)".

EN

Fuel and oil suction and delivery hose

Application: hardwall hose used for the suction and delivery of petroleum products with aromatic content up to 50%.

Temperature: from -20°C (-4°F) to +70°C (+158°F).

Construction

Tube: black, smooth, NBR rubber

Reinforcement: high strength synthetic cord, antistatic copper wire and steel helix wire.

Cover: black, smooth (wrapped finish), synthetic rubber, weathering and oil resistant.

Branding: continuous red spiral stripe "OIL (family logo) PUERTORICO S&D 16 BAR 235 PSI S.F. 3:1 (IVG stripe & web site)