

ARMOFLEX

Code 4480



I. Diam. Toll. EN ISO 1307 [mm]	E. Diam. [mm]	Pitch [mm]	Wire Diam. [mm]	Weight +/-5% [g/m]	PN/bar at 20°C [bar]	Coil length max. [m]
10	16	5,5	0,8	200	10	30
12	18	6,0	0,8	210	9	30
13	19	6,0	0,8	220	9	50
14	20	6,0	0,8	230	9	50
16	22	6,5	0,8	260	9	50
18	24	7,0	1,0	320	8	50
19	25	7,0	1,0	350	8	50
20	27	7,0	1,0	360	8	50
22	29	7,0	1,0	440	8	50
25	33	7,5	1,0	500	8	50
28		8,0				
30	38	8,0	1,0	600	8	50
32	40	8,0	1,2	680	8	50
35	43	8,5	1,2	780	7,5	50
38	47	8,5	1,2	820	7	50
40	49	8,5	1,2	900	7	50
42	51	8,5	1,2	920	6,5	50
45	54	8,5	1,5	1100	6	50
51	61	9,5	1,5	1280	5	50
51	62	9,5	1,8	1390	5	50
60	71	10,0	1,8	1750	5	50
63	75	10,25	1,8	1800	5	50
65	77	10,5	1,8	1920	5	50
70	82	10,5	2,2	2100	4,5	50
76	88	11,0	2,2	2400	4	50
80	93	11,0	2,2	2570	4	50
90	103	13,0	2,2	2950	4	50
102	116	13,0	2,5	3800	3	30
110	125	13,0	2,5	4200	3	20
120		13,0				
127	143	15,0	2,5	4800	3	20
130		15,0				
140		15,5				
152	169	15,5	3	6500	2	20
160		15,5				
180		15,5				
203		20,0				
254		24,0				
305		28,0				

Description:

Thermoplastic suction / discharge hose

heavy duty spiral-reinforced hose for water, potable water, mud, dung, industrial cleaning a.o. and only for lead through of non fatty liquid foodstuffs. Flexible and kink-proof.

Construction:

- final code 000 transparent thermoplastic soft PVC,
- final code 004 white thermoplastic soft PVC,
outside smooth, fully incorporated steel wire helix.

Temperature range:

-15 °C / +60 °C

Bending radius:

3x inside diameter

Vacuum:

0,9 bar

Norm:

EC 1935/2004, LFGB,
EU 10/2011 category: A-B-C-E
food contact 5 min / 70°C.
Contact ratio: 60 cm² / 23 ml.

